


XtremeFLEX® BIH-G Grounded Heavy Insulated Heating Tapes

Product Highlights

- ✓ Grounded for your safety
- ✓ Exceptional flexibility
- ✓ Rapid thermal response
- ✓ Exceptional durability
- ✓ Suitable for electrically conductive surfaces
- ✓ Includes high-temperature tie-downs for easy installation



With Ground

Specifications:



- Maximum exposure temperature: 482°F (250°C)
- Patented grounded heating element
- Polyimide film wrapped fiberglass knitted and braided construction
- Fiberglass outer sheath
- Power density: 9.6 watts/in² (0.015 watts/mm²)
- 120 or 240VAC
- 24" (610mm) lead wire

Ordering Information:

Width in (mm)	Length in (mm)	Total Watts	Part No. 120VAC	Part No. 240VAC
1 (25)	24 (610)	230	BIH101020LG	BIH102020LG
1 (25)	48 (1220)	460	BIH101040LG	BIH102040LG
1 (25)	72 (1830)	690	BIH101060LG	BIH102060LG
1 (25)	96 (2440)	920	BIH101080LG	BIH102080LG
1 (25)	120 (3050)	1150	BIH101100LG	BIH102100LG

RH Plastic Bending Strip Heaters

- ✓ Quickly softens acrylic sheets for easy bending
 - Plastic photos frames
 - Arts and crafts
 - Custom work shop fabricating
- ✓ Provides radiant line of heat. Heater never comes in contact with the plastic
- ✓ Easy-to-use. Designed for production and craft makers



Specifications:

- Multi-stranded resistance wire reinforced with fiberglass knit and braided construction provides even heat across surface
- Power density: 8.6 watts/in² (0.013 watts/mm²)
- Maximum exposure temperature: 900°F (482°C)
- Connects with standard two-prong separable 110VAC electrical plug
- Includes heating element and instructions for building complete strip heater. Other materials are required.

Requires temperature control or supervision while in operation.

Ordering Information:

Width in (mm)	Length in (mm)	Total Watts	Part Number
1/2 (13)	24 (610)	105	RH24
1/2 (13)	36 (915)	157	RH36
1/2 (13)	48 (1220)	209	RH48

IMPORTANT: Temperature controller is required for these products. See pages 80 through 100 for options.

